# SAFETY DATA SHEET

IX-5632 Mar 25, 2015

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: IX-5632

Version =

1.0

Product Name: Spray and Wipe Stain Base

Revision Date: Mar 25, 2015 Date Printed: Mar 25, 2015

Supersedes Date : N.A.

Manufacturer's Name : Ceramic Industrial Coatings

Address: 325 Highway 81 Osseo, MN, US, 55369

Emergency Phone: Chemtrec: 1.800.424.9300

Information Phone : 763-424-2044

Product/Recommended Uses: Wood Stain

# **SECTION 2) HAZARDS IDENTIFICATION**

### Classification:

Aspiration Hazard - Category 1

Germ Cell Mutagenicity - Category 1B

Carcinogenicity - Category 1B

Reproductive Toxicity - Category 2

Flammable Liquid Category 2

# **Pictograms:**





### Signal Word:

Danger

## **Hazardous Statements - Physical:**

Highly flammable liquid and vapor

# **Hazardous Statements - Health:**

May be fatal if swallowed and enters airways

Causes serious eye irritation

May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Suspected of damaging fertility or the unborn child (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 1 of 7

#### **Hazardous Statements - Environmental:**

Not classified

### **Precautionary Statements - Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof <electrical/ventilating/lighting/...> equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

#### **Precautionary Statements - Response:**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/?

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water <or shower>.

In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.

### **Precautionary Statements - Storage:**

Store locked up.

# **Precautionary Statements - Disposal:**

Dispose of contents/container to disposal recycling center.

Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

# **SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

CAS	Chemical Name	% by Weight
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	59% - 98%
NA	Alkyd Resin	6% - 13%
0008032-32-4	NAPHTHA, VM&P	6% - 12%
0068953-58-2	QUARTERNARY AMMONIUM CPDS, BIS (HYDROGENATED TALLOW ALKYL) DIMETHYL-SALT	0.2% - 2.5%

# **SECTION 4) FIRST-AID MEASURES**

## Inhalation:

Take precautions to ensure your own safety. (e.g. wear appropriate protective equipment. Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

#### Skin Contact:

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention. Store contaminated clothing under water and wash before re-use.

# **Eye Contact:**

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 2 of 7

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

# Ingestion:

Rinse mouth. If you feel unwell/concerned: Get medical advice/attention.

### **SECTION 5) FIRE-FIGHTING MEASURES**

# **Suitable Extinguishing Media:**

Use dry chemical, foam or carbon dioxide to extinguish fire.

### **Unsuitable Extinguishing Media:**

Not available.

### **Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done so safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

#### **Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Care should always be exercised in dust/mist areas.

Use water to keep fire-exposed containers and the surroundings cool.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Recommended Equipment:**

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

#### **Personal Precautions:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

#### **Emergency Procedure:**

Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Collect with absorbent, non-combustible material into suitable containers.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

# **Environmental Precautions:**

Do not flush to sewer or waterways. Prevent release to the environment if possible.

# **SECTION 7) HANDLING AND STORAGE**

# General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

#### **Ventilation Requirements:**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

### **Storage Room Requirements:**

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 3 of 7

Keep in a cool, dry, well-ventilated area, away from any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 8) EXPOSURE CONTROLS/ PERSONAL PROTECTION**

### **Eye Protection:**

Dust-proof goggles or safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

#### **Skin Protection:**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. To prevent skin contact wear protective clothing covering all exposed areas. Avoid unnecessary skin contact.

# **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA- Tables- Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
AROMATIC HYDROCARBON MIXTURE >C9	500	2000			1							
NAPHTHA, VM&P									350			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
AROMATIC HYDROCARBON MIXTURE >C9							
NAPHTHA, VM&P							

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

### **Physical and Chemical Properties**

Density	7.41339 lb/gal	
% Solids By Weight	11.23810%	
% VOC	88.02594%	
Appearance	Liquid	
Odor Description	Solvent	
Odor Threshold	N.A.	
рН	N.A.	
Melting Point	N.A.	
Freezing Point	N.A.	
Low Boiling Point	N.A.	
High Boiling Point	N.A.	
Flash Point Symbol	N.A.	
Flash Point	50 °F	

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 4 of 7

Evaporation Rate	N.A.
Flammability	N/A
Upper Explosion Level	N.A.
Lower Explosion Level	N.A.
Vapor Density	N.A.
Vapor Pressure	N.A.
Water Solubility	N.A.
Coefficient Water/Oil	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Viscosity	N.A.

# **SECTION 10) STABILITY AND REACTIVITY**

# Stability:

Stable under normal conditions and use.

#### **Conditions to Avoid:**

Avoid great heat, sparks, flame, build up of static electricity and contact with incompatible materials.

Avoid temperature above maximum storage temperature.

# **Hazardous Polymerization:**

Will not occur.

# **Incompatible Materials:**

Not available.

### **Hazardous Decomposition Products:**

No data available.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

#### Skin Corrosion/Irritation:

Causes mild skin irritation.

# Serious Eye Damage/Irritation:

Causes serious eye irritation.

### Respiratory/Skin Sensitization:

May cause an allergic skin reaction

#### **Germ Cell Mutagenicity:**

May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

## Carcinogenicity:

May cause cancer.

May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

### **Reproductive Toxicity:**

Suspected of damaging fertility or the unborn child (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

# **Specific Target Organ Toxicity - Single Exposure:**

No data available.

# **Specific Target Organ Toxicity - Repeated Exposure:**

No data available.

### **Aspiration Hazard:**

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 5 of 7

May be fatal if swallowed and enters airways

## **Acute Toxicity:**

No data available.

Potential Health Effects - Miscellaneous

0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

# **SECTION 12) ECOLOGICAL INFORMATION**

#### Toxicity:

No data available.

### Persistence and Degradability:

No data available.

#### **Bioaccumulative Potential:**

No data available.

# Mobility in Soil:

No data available.

#### Other Adverse Effects:

No data available.

### **SECTION 13) DISPOSAL CONSIDERATIONS**

# Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 14) TRANSPORT INFORMATION**

#### **U.S. DOT Information:**

Shipping Name: Paint related material

UN/NA #: 1263 Hazard Class:3 Packing Group: II

Required Label(s): Flammable Placards: Combustible

# **IMDG Information:**

Shipping Name: Paint related material

UN/NA #: 1263 Hazard Class:3 Packing Group: III

Required Label(s): Combustible

### **IATA Information:**

Shipping Name: Paint related material

UN/NA #: 1263 Hazard Class:3 Packing Group: II

Required Label(s): Combustible

# **SECTION 15) REGULATORY INFORMATION**

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 6 of 7

CAS	Chemical Name	% By Weight	Regulation List
0008032-32-4	NAPHTHA, VM&P	6% - 12%	SARA312,TSCA
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	59% - 98%	SARA312,TSCA
0068953-58-2	QUARTERNARY AMMONIUM CPDS, BIS (HYDROGENATED TALLOW ALKYL) DIMETHYL-SALT	0.2% - 2.5%	SARA312,TSCA

# SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

# Glossary:

ACGIH: American Conference of Governmental Industrial Hygienists

ANSI: American National Standards Institute

Canadian TDG: Canadian Transportation of Dangerous Goods

CAS: Chemical Abstract Service

Chemtrec: Chemical Transportation Emergency Center (US)

CHIP: Chemical Hazard Information and Packaging

DSL: Domestic Substances List

EC: Equivalent Concentration

EH40 (UK): HSE Guidance Note EH40 Occupational Exposure Limits EPCRA: Emergency Planning and Community Right-To-Know Act

HMIS: Hazardous Material Information Service

LC: Lethal Concentration

LD: Lethal Dose

NFPA: National Fire Protection Association

OEL: Occupational Exposure Limits OSHA: Occupational Safety and Health Administration, US Department of Labor

PEL: Permissible Exposure Limit

SARA (Title III): Superfund Amendments and Reauthorization Act

SARA 313: Superfund Amendments and Reauthorization Act, Section 313

SCBA: Self-Contained Breathing Apparatus

STEL: Short Term Exposure Limit


TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act Public Law 94-469

TWA: Time Weighted Value

US DOT: US Department of Transportation

WHMIS: Workplace Hazardous Materials Information System



# **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

ERA\_EHS 7.02 Report Code M007 www.paints.com Page 7 of 7