

# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

**Product ID:** PB-7834  
**Product Name:** EnviroPrime Zero  
**Revision Date:** Jul 06, 2017 **Date Printed:** Jul 06, 2017  
**Version:** 1.0 **Supersedes Date:** N.A.  
**Manufacturer's Name:** Ceramic Industrial Coatings  
**Address:** 325 Highway 81 Osseo, MN, US, 55369  
**Emergency Phone:** Chemtrec: 1.800.424.9300  
**Information Phone Number:** 763-424-2044  
**Fax:**  
**Product/Recommended Uses:** Paint or paint additive

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3  
Skin Irritation - Category 2  
Carcinogenicity - Category 2  
Reproductive Toxicity - Category 2  
Eye Irritation - Category 2  
Acute aquatic toxicity - Category 3  
Flammable Liquids - Category 2  
Acute toxicity Oral - Category 5

### Precautionary Statements - General

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.

### Pictograms



### Precautionary Statements - Disposal

Dispose of contents/container to disposal recycling center.  
Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.  
See recommendations in section 7 for handling and disposal of contaminated articles.

### Signal Word

Danger

### Hazardous Statements - Health

May cause drowsiness or dizziness  
Causes skin irritation  
Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes serious eye irritation

May be harmful if swallowed

#### **Hazardous Statements - Physical**

Highly flammable liquid and vapor

#### **Hazardous Statements - Environmental**

Harmful to aquatic life

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Keep container tightly closed.

Wash hands and face thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid release to the environment.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

#### **Precautionary Statements - Response**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Specific treatment (see details on this label).

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing. And wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

In case of fire: Use material listed in SDS section 5 to extinguish.

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Store locked up.

Store locked up.

Store in a well-ventilated place. Keep cool.

**Acute toxicity of 1.66% of the mixture is unknown**

---

### **SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS**

---

<b>CAS</b>	<b>Chemical Name</b>	<b>% By Weight</b>
0013463-67-7	TITANIUM DIOXIDE	13% - 27%
0000123-86-4	BUTYL ACETATE	12% - 25%
0007727-43-7	BARIUM SULFATE	10% - 20%
0000064-17-5	ETHYL ALCOHOL	8% - 17%
0066070-62-0	ALKYD RESIN	7% - 14%

---

0014807-96-6	TALC	4.0% - 8%
0009004-70-0	NITROCELLULOSE	0.4% - 4.2%
0000067-63-0	ISOPROPYL ALCOHOL	0.4% - 4.1%
0000141-78-6	ETHYL ACETATE	0.2% - 1.6%
0007631-86-9	SILICA, AMORPHOUS	0.1% - 1.4%
0000071-36-3	N-BUTYL ALCOHOL	0.1% - 1.0%
0000108-83-8	DIISOBUTYL KETONE	0.1% - 0.7%
0000110-43-0	METHYL N-AMYL KETONE	0.0% - 0.3%
0000701-64-4	MONOPHENYL PHOSPHORIC ACID	0.0% - 0.2%
0000100-41-4	ETHYLBENZENE	0.0% - 0.2%
0000109-60-4	N-PROPYL ACETATE	0.0% - 0.2%
0001330-20-7	XYLENE	0.0% - 0.1%
0000095-47-6	O-XYLENE	0.0% - 0.1%
0000108-38-3	M-XYLENE	0.0% - 0.1%
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	0.0% - 0.1%
0000106-42-3	P-XYLENE	0.0% - 0.1%
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace
0000108-95-2	PHENOL	Trace
0000057-55-6	PROPYLENE GLYCOL	Trace
0000078-83-1	ISOBUTYL ALCOHOL	Trace
0000108-82-7	DIISOBUTYLCARBINOL (ODOR)	Trace
0000111-66-0	1-OCTENE	Trace
0000108-88-3	TOLUENE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

## SECTION 4) FIRST-AID MEASURES

---

### Inhalation

Take precautions to ensure your own safety. (e.g. wear appropriate protective equipment. Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention. Store contaminated clothing under water and wash before re-use.

### Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

### Ingestion

Rinse mouth. If you feel unwell/concerned: Get medical advice/attention.

---

## SECTION 5) FIRE-FIGHTING MEASURES

---

### Suitable Extinguishing Media

Use dry chemical, foam or carbon dioxide to extinguish fire.

### Unsuitable Extinguishing Media

Not available.

### Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done so safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

### Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Care should always be exercised in dust/mist areas.

Use water to keep fire-exposed containers and the surroundings cool.

---

## SECTION 6) ACCIDENTAL RELEASE MEASURES

---

### Recommended Equipment

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### Emergency Procedure

Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Collect with absorbent, non-combustible material into suitable containers.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

### Environmental Precautions

Do not flush to sewer or waterways. Prevent release to the environment if possible.

---

## SECTION 7) HANDLING AND STORAGE

---

### General

Wash hands after use.  
Do not get in eyes, on skin or on clothing.  
Do not breathe vapors or mists.  
Use good personal hygiene practices.  
Eating, drinking and smoking in work areas is prohibited.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Eyewash stations and showers should be available in areas where this material is used and stored.

### Ventilation Requirements

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

### Storage Room Requirements

Keep in a cool, dry, well-ventilated area, away from any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

---

## SECTION 8) EXPOSURE CONTROLS/ PERSONAL PROTECTION

---

### Eye Protection

Dust-proof goggles or safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

### Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. To prevent skin contact wear protective clothing covering all exposed areas. Avoid unnecessary skin contact.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
---------------	----------------------	------------------------	-----------------------	-------------------------	--------------------------------	--------------------	-----------------------------	-----------------------	-------------------------	------------------------	--------------------------	---------------------

AROMATIC HYDROCARBON MIXTURE >C9	500	2000			1						
BARIUM SULFATE		[15]; [5 (a)];			1			10,5a			
BUTYL ACETATE	150	710			1		150	710	200	950	
DIISOBUTYL KETONE	50	290			1		25	150			
ETHYL ACETATE	400	1400			1		400	1400			
ETHYL ALCOHOL	1000	1900			1		1000	1900			
ETHYLBENZENE	100	435			1		100	435	125	545	
ISOBUTYL ALCOHOL	100	300			1		50	150			
ISOPARAFFINIC PETROLEUM DISTILLATE	500	2000			1						
ISOPROPYL ALCOHOL	400	980			1		400	980	500	1225	
METHYL N-AMYL KETONE	100	465			1		100	465			
M-XYLENE	100	435			1		100	435	150	655	
N-BUTYL ALCOHOL	100	300			1						
N-PROPYL ACETATE	200	840			1		200	840	250	1050	
O-XYLENE	100	435			1		100	435	150	655	
PHENOL	5	19			1	1	5	19			
P-XYLENE	100	435			1		100	435	150	655	
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2			1,3			6			
TALC		20 mppcf			1	1					
TITANIUM DIOXIDE		15			1		b				1
TOLUENE	200 (a)/ 300 ceiling	0.2	500ppm /10 minutes (a)		1,2		100	375	150	560	
XYLENE	100	435			1		100	435	150	655	

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
AROMATIC HYDROCARBON MIXTURE >C9							
BARIUM SULFATE		5 (I)(E)			A4	A4	Pneumocniosis
BUTYL ACETATE	50		150				Eye & URT irr
DIISOBUTYL KETONE	25	145					URT & eye irr
ETHYL ACETATE	400	1440					URT & eye irr
ETHYL ALCOHOL			1000		A3	A3	URT irr

ETHYLBENZENE	20				A3	A3; BEI	URT irr; Kidney dam (nephropathy); Cochlear impair
ISOBUTYL ALCOHOL	50	152					Skin & eye irr
ISOPARAFFINIC PETROLEUM DISTILLATE							
ISOPROPYL ALCOHOL	200		400		A4	A4; BEI	Eye & URT irr; CNS impair
METHYL N-AMYL KETONE	50	233					Eye & skin irr
M-XYLENE	100	434	150	651	A4	A4; BEI	URT & eye irr; CNS impair
N-BUTYL ALCOHOL	20						Eye & URT irr
N-PROPYL ACETATE	200	835	250	1040			Eye & URT irr
O-XYLENE	100	434	150	651	A4	A4; BEI	URT & eye irr; CNS impair
PHENOL	5	19			A4	Skin; A4; BEI	URT irr; lung dam; CNS impair
P-XYLENE	100	434	150	651	A4	A4; BEI	URT & eye irr; CNS impair
SILICA, AMORPHOUS							
TALC	0.1 f/cc (F) (K)	2 (E,R)			[A1]; [A4];	[A1]; [A4];	[LRT irr]; [Pneumocociosis; lung cancer; mesothelioma];
TITANIUM DIOXIDE		10			A4	A4	LRT irr
TOLUENE	20	0.2			A4	A4; BEI	Visual impair; female repro; pregnancy loss
XYLENE	100	434	150	651	A4	A4; BEI	URT & eye irr; CNS impair

(C) - Ceiling limit, (F) - Respirable fibers, (K) - Should not exceed 2 mg/m3 respirable particulate mass, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, impair - Impairment, irr - Irritation, LRT - Lower respiratory tract, repro - reproductive, URT - Upper respiratory tract

---

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

---

### Physical and Chemical Properties

Density	11.994230 lb/gal
% Solids By Weight	60.467100%
% VOC	39.435020%

---

Appearance	Liquid
------------	--------

Odor Description	Solvent
Odor Threshold	N.A.
pH	N.A.
Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Flash Point Symbol	N.A.
Flash Point	24 °F
Evaporation Rate	N.A.
Flammability	N/A
Upper Explosion Level	N.A.
Lower Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Water Solubility	N.A.
Coefficient Water/Oil	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Viscosity	N.A.

---

## SECTION 10) STABILITY AND REACTIVITY

---

### Stability

Stable under normal conditions and use.

### Conditions to Avoid

Avoid temperature above maximum storage temperature.

Avoid great heat, sparks, flame, build up of static electricity and contact with incompatible materials.

### Hazardous Polymerization

Will not occur.

### Incompatible Materials

Not available.

### Hazardous Decomposition Products

No data available.

---

## SECTION 11) TOXICOLOGICAL INFORMATION

---

### Aspiration Hazard

No Data Available

### Germ Cell Mutagenicity

No Data Available

### Respiratory/Skin Sensitization

No Data Available

### Specific Target Organ Toxicity - Repeated Exposure

No Data Available

### Acute Toxicity

May be harmful if swallowed

### Carcinogenicity

### Reproductive Toxicity

### Serious Eye Damage/Irritation

Causes serious eye irritation

### **Skin Corrosion/Irritation**

Causes skin irritation

### **Specific Target Organ Toxicity - Single Exposure**

May cause drowsiness or dizziness

#### 0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m<sup>3</sup> (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

#### 0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

#### 0000071-36-3 N-BUTYL ALCOHOL

LC50 (rat): greater than 8000 ppm (4-hour exposure) (14)

LD50 (oral, rat): 2510 mg/kg (15)

LD50 (oral, male rat): 790 mg/kg (16)\*

LD50 (oral, female rat): 2020 mg/kg (16)\* \*(Note: the rats used in this study appear to have been very young (60-100 grams).)

LD50 (oral, hamster): 1200 mg/kg (11, original)

#### 0000078-83-1 ISOBUTYL ALCOHOL

LD50 (oral, rat): 2460 mg/kg.(7)

LD50 (oral, rabbit): 3000 mg/kg (reported as 41 mmol/kg) (8)

LD50 (dermal, rabbit): 3400 mg/kg (reported as 4.24 mL/kg).(7)

#### 0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)

LD50 (oral, rat): 4.72 g/kg (3,5,7,8)

LD50 (dermal, rabbit): 17.8 g/kg (11)

#### 0000108-88-3 TOLUENE

LC50 (rat): 8800 ppm (4-hour exposure) (2)

LC50 (rat): 6000 ppm (6-hour exposure) (3)

LD50 (oral, rat): 2600 to 7500 mg/kg (3,5,11,17)

LD50 (oral, neonatal rat): less than 870 mg/kg (3)

LD50 (dermal, rabbit): 12,225 mg/kg (reported as 14.1 ml/kg) (1)

#### 0000123-86-4 BUTYL ACETATE

LC50 (rat): 1802 mg/m<sup>3</sup>; 4-hour exposure (aerosol)(9) Note: A lower LC50 (aerosol) value of 760 mg/m<sup>3</sup> (160 ppm); 4-hour exposure has been reported.(11,27) Extensive research has failed to confirm this value.

LD50 (oral, rat): 10770 mg/kg (12, unconfirmed)

LD50 (oral, mouse): 7100 mg/kg (5)

LD50 (oral, rabbit): 7400 mg/kg (cited as 64 millimols/kg) (13)

LD50 (dermal, rabbit): Greater than 5000 mg/kg (3, unconfirmed)

#### 0000141-78-6 ETHYL ACETATE

LC50 (rat): 19600 ppm (4-hour exposure); cited as 16000 ppm (6-hour exposure) (10)

LC50 (mouse): 10600 ppm (38100 mg/m<sup>3</sup>) (4-hour exposure); cited as 44000 mg/m<sup>3</sup> (3-hour exposure) (8)

LD50 (oral, rat): 10200 mg/kg (cited as 11.3 mL/kg) (7); 5600 mg/kg (5,13)

LD50 (oral, mouse): 4100 mg/kg (11)

LD50 (oral, rabbit): 4900 mg/kg (9)

LD50 (oral, guinea pig): 5500 mg/kg (11)

LD50 (dermal, rabbit): Greater than 18000 mg/kg (cited as 20 m



0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1)LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)  
LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene)(2)  
LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1)LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)  
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)  
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)  
LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)  
LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)  
LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

0000108-95-2 PHENOL

LD50 (oral, rat): 340 mg/kg (20% solution) (16)  
LD50 (oral, rat): 530 mg/kg (2 and 5% solutions) (16)  
LD50 (oral, rat): 320 mg/kg (cited as 0.30 cc/kg) (17)  
LD50 (dermal, pig): 500 mg/kg (liquefied phenol (45 deg C)) (2/3 animals died) (18)  
LD50 (derm

0000110-43-0 METHYL N-AMYL KETONE

LC100 (rat): 4,000 ppm (4-hour exposure) (8)  
LD50 (oral, female rat): 1,670 mg/kg (8)  
LD50 (oral, mouse): 730 mg/kg (3; not confirmed)  
LD50 (oral, mouse): 2,390 mg/kg; reported as 21.08 mmol/kg (7)  
LD50 (dermal, rabbit): 10,300 mg/kg; reported as 12.6 mL/kg (8)

0000108-83-8 DIISOBUTYL KETONE

LD50 (oral, rat): 5800 mg/kg (1)  
LD50 (oral, mouse): 1416 mg/kg (2; original report unpublished)  
LD50 (oral, mouse): 2800 mg/kg (3)  
LD50 (dermal, rabbit): 1600 mg/kg (1)

0000108-38-3 M-XYLENE

LC50 (rat): 7330 ppm (4-hour exposure); cited as 5984 ppm (6-hour exposure) (3,17)  
LC50 (mouse): 6450 ppm (4-hour exposure); cited as 5267 ppm (6-hour exposure) (3)  
LD50 (oral, rat): 5011 mg/kg (3); 6660 mg/kg (3)  
LD50 (dermal, rabbit): 12180 mg/kg (3,17)

0000106-42-3 P-XYLENE

LC50 (rat): 4740 ppm (4-hour exposure) (3)  
LC50 (mouse): 4800 ppm (4-hour exposure); cited as 3900 ppm (6-hour exposure) (1,4,6)  
LD50 (oral, rat): 4030 mg/kg (3); 4550 mg/kg (10)

0000095-47-6 O-XYLENE

LC50 (rat): 5300 ppm (4-hour exposure); cited as 4330 ppm (6-hour exposure) (3)  
LC50 (mouse): 5630 ppm (4-hour exposure); cited as 4595 ppm (6-hour exposure) (3,4)  
LD50 (oral, rat): 3608 mg/kg (3,16)  
LD50 (dermal, rabbit): 20000 mg/kg (3)

0000109-60-4 N-PROPYL ACETATE

LD50 (oral, rat): 8700 mg/kg; cited as 9.8 mL/kg (4)  
LD50 (oral, mouse): 8300 mg/kg (5)  
LD50 (oral, rabbit): 6600 mg/kg; cited as 65 mmols/kg (6)  
LD50 (dermal, rabbit): Greater than 17700 mg/kg; cited as 20 mL/kg (4)

**Chronic Exposure**

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0000108-88-3 TOLUENE

TERATOGENIC EFFECTS:Toluene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

**Potential Health Effects - Miscellaneous**

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000071-36-3 N-BUTYL ALCOHOL

May cause abnormal blood forming function with anemia. Liquid splashes in the eye may result in chemical burns.

0000078-83-1 ISOBUTYL ALCOHOL

Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. May cause irritation of the mucous membranes. May cause abnormal liver function. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: bone marrow, liver. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000108-83-8 DIISOBUTYL KETONE

The following medical conditions may be aggravated by exposure: asthma, blood, dermatitis. Contact may cause skin irritation with discomfort or rash. Repeated exposure may cause allergic skin rash, itching, swelling. This substance may cause damage to any of the following organs/systems: eyes, kidneys, liver. Extremely high oral and inhalation doses in laboratory animals have shown weight changes in various organs such as the liver, kidney, brain, heart and adrenal gland. In addition liver and kidney injury were observed at the extremely high inhalation level. In another inhalation study there was a slight depression in the white blood cell count. Liquid or vapor causes irritation, experienced as stinging, excess blinking and tear production, with excess redness and swelling of the conjunctiva.

0000108-88-3 TOLUENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

0000123-86-4 BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0000141-78-6 ETHYL ACETATE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0009004-70-0 NITROCELLULOSE

The following medical conditions may be aggravated by overexposure: liver disease, kidney disorders.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m<sup>3</sup> respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m<sup>3</sup> level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.'

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

---

## SECTION 12) ECOLOGICAL INFORMATION

---

### Toxicity

No data available.

Harmful to aquatic life

### Persistence and Degradability

No data available.

### Bioaccumulative Potential

No data available.

### Mobility in Soil

No data available.

### Other Adverse Effects

No data available.

### Bio-accumulative Potential

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Contains constituents with the potential to bio accumulate.

### Mobility in Soil

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Floats on water. Contains volatile constituents. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.

### Persistence and Degradability

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

---

## SECTION 13) DISPOSAL CONSIDERATIONS

---

### Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

---

## SECTION 14) TRANSPORT INFORMATION

---

### U.S. DOT Information

Shipping Name: Paint related material  
 UN/NA #: 1263 Hazard Class:3 Packing Group: II  
 Required Label(s): Flammable  
 Placards: Combustible

### IMDG Information

Shipping Name: Paint related material  
 UN/NA #: 1263 Hazard:3 Packing Group: II  
 Required Label(s): Combustible

### IATA Information

**SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0013463-67-7	TITANIUM DIOXIDE	13% - 27%	SARA312,TSCA,CA_Carcinogen,ND_TOX,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0000123-86-4	BUTYL ACETATE	12% - 25%	CERCLA,SARA312,TSCA,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0007727-43-7	BARIUM SULFATE	10% - 20%	SARA312,TSCA,CA_TOX,ND_TOX
0000064-17-5	ETHYL ALCOHOL	8% - 17%	SARA312,TSCA,MI_TOX,ND_TOX,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0066070-62-0	ALKYD RESIN	7% - 14%	SARA312,TSCA
0014807-96-6	TALC	4.0% - 8%	SARA312,TSCA,CA_TOX,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0009004-70-0	NITROCELLULOSE	0.4% - 4.2%	SARA312,TSCA
0000067-63-0	ISOPROPYL ALCOHOL	0.4% - 4.1%	SARA312,TSCA,CA_TOX,MI_TOX,ND_TOX
0000141-78-6	ETHYL ACETATE	0.2% - 1.6%	CERCLA,SARA312,TSCA,RCRA,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0007631-86-9	SILICA, AMORPHOUS	0.1% - 1.4%	SARA312,TSCA,MI_TOX,ND_TOX
0000071-36-3	N-BUTYL ALCOHOL	0.1% - 1.0%	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TOX,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-83-8	DIISOBUTYL KETONE	0.1% - 0.7%	SARA312,TSCA,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000110-43-0	METHYL N-AMYL KETONE	0.0% - 0.3%	SARA312,TSCA,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000701-64-4	MONOPHENYL PHOSPHORIC ACID	0.0% - 0.2%	SARA312,TSCA,MI_TOX
0000100-41-4	ETHYLBENZENE	0.0% - 0.2%	SARA313, CERCLA,SARA312,TSCA,CA_TAC_TOX,CA_TOX,CA_Carcinogen,MI_TOX,MN_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0000109-60-4	N-PROPYL ACETATE	0.0% - 0.2%	SARA312,TSCA,ND_TOX
0001330-20-7	XYLENE	0.0% - 0.1%	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,MI_TOX,MN_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0000095-47-6	O-XYLENE	0.0% - 0.1%	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,CA_TOX,MI_TOX,MN_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-38-3	M-XYLENE	0.0% - 0.1%	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,CA_TOX,MI_TOX,MN_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	0.0% - 0.1%	SARA312,TSCA,MI_TOX
0000106-42-3	P-XYLENE	0.0% - 0.1%	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,CA_TOX,MI_TOX,MN_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0064742-95-6	AROMATIC HYDROCARBON MIXTURE >C9	Trace	SARA312,TSCA,MI_TOX

0000108-95-2	PHENOL	Trace	SARA313, CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,CA_TOX,MI_TOX,MN_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern -High Production Volume (2006 and 3 of 4 years)
0000057-55-6	PROPYLENE GLYCOL	Trace	SARA312,TSCA,MI_TOX
0000078-83-1	ISOBUTYL ALCOHOL	Trace	CERCLA,SARA312,TSCA,RCRA,MI_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000108-82-7	DIISOBUTYL CARBINOL (ODOR)	Trace	SARA312,TSCA
0000111-66-0	1-OCTENE	Trace	SARA312,TSCA
0000108-88-3	TOLUENE	Trace	CERCLA,SARA312,TSCA,RCRA,CA_TAC_TOX,CA_TOX,MI_TOX,MN_TOX,ND_TOX,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Develop - CA_Proposition65_Type_Toxicity_Developmental,MN_ChemHighConcern - Minnesota Chemicals of High Concern list,MN_ChemHighConcern_HP_V_2006_3_of_4_years - Minnesota - Chemicals High Concern - High Production Volume (2006 and 3 of 4 years)

## SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

### Glossary

ACGIH: American Conference of Governmental Industrial Hygienists  
ANSI: American National Standards Institute  
Canadian TDG: Canadian Transportation of Dangerous Goods  
CAS: Chemical Abstract Service  
Chemtrec: Chemical Transportation Emergency Center (US)  
CHIP: Chemical Hazard Information and Packaging  
DSL: Domestic Substances List  
EC: Equivalent Concentration  
EH40 (UK): HSE Guidance Note EH40 Occupational Exposure Limits  
EPCRA: Emergency Planning and Community Right-To-Know Act  
HMIS: Hazardous Material Information Service  
LC: Lethal Concentration  
LD: Lethal Dose  
NFPA: National Fire Protection Association  
OEL: Occupational Exposure Limits OSHA: Occupational Safety and Health Administration, US Department of Labor  
PEL: Permissible Exposure Limit  
SARA (Title III): Superfund Amendments and Reauthorization Act  
SARA 313: Superfund Amendments and Reauthorization Act, Section 313  
SCBA: Self-Contained Breathing Apparatus  
STEL: Short Term Exposure Limit  
TLV: Threshold Limit Value  
TSCA: Toxic Substances Control Act Public Law 94-469  
TWA: Time Weighted Value  
US DOT: US Department of Transportation  
WHMIS: Workplace Hazardous Materials Information System

### HMIS

Health	/ 2
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	X

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### Version 1.0:

Revision Date: Jul 06, 2017

---

**DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.